

N94-15567

An improved light source for laser ranging

Karel Hamal
Technical University
Prague, Czechoslovakia
Tel 422 46 23 97
Fax 422 847688

and

Martin Richardson
CREOL
University of Central Florida
Orlando, USA
Tel 407 658 6819
Fax 407 658 6880

Summary

The development of a new laser material, Cr-doped LiSAF makes possible the development of a laser source for satellite ranging systems that is superior in performance capabilities than current Nd:YAG-based laser sources. This new material offers the potential of shorter pulses and more preferable wavelengths (850nm and 425nm) than multi-wavelength Nd:YAG systems, leading to superior ranging resolution and greater detection sensitivity.

We are embarking on a feasibility study of a two-wavelength , mode-locked laser system based on Cr:LiSAF, providing shorter pulses for improved ranging resolution.

Background

Current satellite multi-wavelength laser-ranging systems operating with Nd:YAG based systems are capable of resolving earth-satellite distances to within a centimeter. The latter limitation is primary set by the minimum pulse-duration available from current field-usable mode-locked Nd:YAG laser systems having diffraction-limited beam divergence. Recent developments in ultrashort laser pulse technology with a new laser material perfected at CREOL in the last two years, now offers the possibility of an improved multi-wavelength laser-ranging system. The principal advantages this new material will offer is in shorter laser pulse durations, down to a few picoseconds, thereby improving ranging accuracy to the millimeter level, and in the use of shorter laser wavelengths permitting detection in a region of higher photocathode sensitivity, thereby improving overall sensitivity.

The new laser material Cr-doped LiSAF¹ has already been extensively studied^{2,3}, and reliable mode-locked operation has been demonstrated⁴. At the present time most of the technology of Cr-doped LiSAF is resident at CREOL. This has occurred as consequence of it's crystal growth development at CREOL, and in a concerted effort being made by CREOL scientists to determine it's optical and physical properties. As a consequence, many laboratories are examining potential applications of this exciting new laser material.

Technical Details

We wish to take advantage of the possibilities offered by Cr:LiSAF in developing a fieldable laser for satellite ranging providing the general properties referred to above. A modelocked Cr:LiSAF laser can be built under this program that would have the principal components shown in fig.1.




Fig.1. Schematic of an actively modelocked multifrequency Cr:LiSAF laser for satellite ranging

A cw single mode diode laser operating at $\sim 845\text{nm}$ can be used to seed the Cr:LiSAF laser with a specific frequency. This will both control the frequency of the laser, and its harmonic, and ensure that the modelocked laser has single mode output itself, ensuring diffraction-limited beam divergence. Short pulses would be formed within the laser with the aid of conventional modelocking and Q-switching techniques. With the laser locked to a specific output frequency, efficient, stable, phase-matched second harmonic conversion will be guaranteed. The output performance of the laser will have the following parameters

Energy per pulse-train	500mJ	Wavelength	850nm
Number of pulses	10	Energy per pulse	50mJ
Pulse-duration	30ps	Pulse separation	10ns
Second Harmonic Conv. Eff.	25%	En. @ 425nm	12.5mJ

References

1. S.A. Payne, L.L. Chase, L.K. Smith, W.L. Kway, and H.W. Newkirk, "Laser performance of $\text{LiSrAlF}_6:\text{Cr}^{3+}$," J. Appl. Phys. **66**, 1051, 1989.
2. P. Beaud, Y-F. Chen, B. Chai, and M. Richardson, "Small-signal gain properties of $\text{LiSrAlF}_6:\text{Cr}^{3+}$," submitted to Optics Letters.
3. Y. F. Chen, P. Beaud, B. H. T. Chai & M. Richardson, "Small signal gain measurements of Cr-doped LiSAF and LiCAF" Proc. Conf. on Advanced Solid State Lasers Santa Fe (Optical Society of America 1992) to be published.
4. P. Beaud, E. Miesak, Y-F. Chen, B. H. T. Chen and M. Richardson, "A flashlamp-pumped Cr:LiSAF regenerative amplifier" Proc. Conf. on Advanced Solid State Lasers Santa Fe (Optical Society of America 1992) to be published.

Epoch and Event Timing

